

2ParkUp Two Tier Bike Rack Specification Detail

Gas-assisted two-tier bike rack

- Supplier: Turvec Solutions Limited
- Tel. 0800 246 5474 www.turvec.com

Dimensions

- Height requirement: 2600mm
- Depth, single-sided: 1900mm
- Depth, double-sided: 2900mm
- Loading distance 1800mm-2000mm
- Spacing: 375mm & 400mm
- Single-sided modules available: 4 bikes, 6 bikes, 8 bikes, 10 bikes, 12 bikes, 14 bikes, 16 bikes.
- Double-sided modules available: 8 bikes, 12 bikes, 16 bikes, 20 bikes, 24 bikes, 28 bikes, 32 bikes.
- Modules fix together resulting in no loss in spacing

Materials

- Steel frame and trays
- High quality industrial gas-spring
- Aluminium gas-spring housing
- Rubber protective forks on lower tier
- Plastic feet
- PE-HM 500 Plastic guider ensures smooth and quiet running of upper tiers

Finish

- Galvanised steel
- Powder coated gas-spring housing

Fixing

- Surface mounted with adjustable feet

Options

- Powder coating frame and trays

Warranty

- 10 years for structural components
- 2 years for gas-spring

Certifications

- Fietsparkeur
- Tested to 20,000 movements with and without a bicycle